

TECHNICAL SPECIFICATIONS T400

POWER OUTPUT (STEREO)	150 WATTS PER CHANNEL INTO 8 OHMS 300 WATTS PER CHANNEL INTO 4 OHMS
POWER OUTPUT (MONO)	450 WATTS INTO 8 OHMS 900 WATTS INTO 4 OHMS
OUTPUT DEVICES:	20 MATCHED IGBT'S PER CHANNEL
FREQUENCY RESPONSE:	DC-100 KHZ (+0dB/-7dB)
DISTORTION:	LESS THAN .01% THD TYPICALLY LESS THAN .1% AT FULL RATED POWER
INPUT IMPEDANCE:	2 K OHM BALANCED 50 K OHM UNBALANCED
DAMPING FACTOR:	GREATER THAN 500 AT 8 OHMS
GAIN FACTOR:	28 dB
INPUT SENSITIVITY:	2.8VOLTS BALANCED, FOR FULL OUTPUT 1.4 VOLTS UNBALANCED
POWER SUPPLY:	2 EA. 500 VACUSTOM POWER TRANSFORMER 128,000 MICROFARADS OF FILTER CAPACITANCE
CURRENT CONSUMPTION:	300 WATTS IDLE
DIMENSIONS:	HEIGHT 93" (23.6 CM) WIDTH 18.3" (46.4 CM) LENGTH 19.4" (49.2 CM)
SHIPPING WEIGHT:	96 LB.S ((43.6 KG)

THRESHOLD
310 CORTEZ CIRCLE
CAMARILLO
CA 93012

CUSTOMER SERVICE 805 / 383-2788
Fax 805 / 383-2794

EMAIL 76711,3570@COMPUSERVE.COM

printed in the USA

PN 057-0200